2N3707 2N3710 2N3708 2N3711 2N3709

SILICON

TO-92 CASE





www.centralsemi.com

DESCRIPTION:

The CENTRAL SEMICONDUCTOR 2N3707 series devices are silicon NPN transistors designed for low level, low noise (2N3707), low level, high gain (2N3708, 2N3709, 2N3710, 2N3711) applications. Recommended PNP complementary series is 2N4058 thru 2N4062.

MARKING: FULL PART NUMBER

•											
	M RATINGS: (T _A =25°C)		MBOL						UNIT	S	
Collector-B	ase Voltage	'	√сво			30			V		
Collector-E	mitter Voltage	'	√CEO			30			V		
Emitter-Bas	se Voltage	'	√EBO			6.0			V		
Continuous	Collector Current		I_{C}			200			mA		
Power Diss	sipation		P_{D}			625			mW	'	
Operating and Storage Junction Temperature		T_J , T_{stg}			-65 to +150			°C			
ELECTRIC	AL CHARACTERISTICS: (T _A =25°C u	ınless	otherw	ise no	ted)						
SYMBOL	TEST CONDITIONS		MIN		,	MAX			UNIT	S	
ICBO	V _{CB} =20V					100			nA		
I _{EBO}	V _{EB} =6.0V					100			nA		
BV_{CEO}	I _C =1.0mA		30						V		
V _{CE} (SAT)	I _C =10mA, I _B =0.5mA					1.0			V		
V _{BE(ON)}	V_{CE} =5.0V, I_{C} =1.0mA		0.5			1.0			V		
NF	V_{CE} =5.0V, I_{C} =100 μ A, R_{G} =10 $K\Omega$,										
	BW=15.7kHz (2N3707 only)					5.0			dB		
			<u>3707</u>		<u>3708</u>		<u> 3709</u>		<u> 3710</u>		<u> 3711</u>
SYMBOL	TEST CONDITIONS	MIN	MAX	MIN	MAX	MIN	MAX	MIN	MAX	MIN	MAX
h _{FE}	V _{CE} =5.0V, I _C =100μA	100	400	-	-	-	-	-	-	-	-
hFE	V _{CE} =5.0V, I _C =1.0mA	100	- 550	45	660	45	165	90	330	180	660
h _{fe} h _{fe}	V_{CE} =5.0V, I_{C} =100 μ A, f=1.0kHz V_{CE} =5.0V, I_{C} =1.0mA, f=1.0kHz	-	-	45	800	- 45	250	90	- 450	180	800


2N3707 2N3710 2N3708 2N3711 2N3709

SILICON

NPN TRANSISTORS



TO-92 CASE - MECHANICAL OUTLINE



DIMENSIONS										
	INC	HES	MILLIMETERS							
SYMBOL	MIN	MAX	MIN	MAX						
A (DIA)	A (DIA) 0.175		4.45	5.21						
В	0.170	0.210	4.32	5.33						
С	C 0.500		12.70	-						
D	0.016	0.022	0.41	0.56						
E	0.1	100	2.54							
F	0.0)50	1.27							
G	G 0.125 C		3.18	4.19						
Н	H 0.080		2.03	2.67						
I	0.0)15	0.38							

TO-92 (REV: R1)

LEAD CODE:

- 1) Emitter
- 2) Collector 3) Base

R1

MARKING:

FULL PART NUMBER

OUTSTANDING SUPPORT AND SUPERIOR SERVICES



PRODUCT SUPPORT

Central's operations team provides the highest level of support to insure product is delivered on-time.

- Supply management (Customer portals)
- · Inventory bonding
- · Consolidated shipping options

- · Custom bar coding for shipments
- · Custom product packing

DESIGNER SUPPORT/SERVICES

Central's applications engineering team is ready to discuss your design challenges. Just ask.

- Free guick ship samples (2nd day air)
- Online technical data and parametric search
- SPICE models
- · Custom electrical curves
- · Environmental regulation compliance
- · Customer specific screening
- · Up-screening capabilities

- Special wafer diffusions
- PbSn plating options
- Package details
- Application notes
- · Application and design sample kits
- Custom product and package development

REQUESTING PRODUCT PLATING

- 1. If requesting Tin/Lead plated devices, add the suffix "TIN/LEAD" to the part number when ordering (example: 2N2222A TIN/LEAD).
- 2. If requesting Lead (Pb) Free plated devices, add the suffix "PBFREE" to the part number when ordering (example: 2N2222A PBFREE).

CONTACT US

Corporate Headquarters & Customer Support Team

Central Semiconductor Corp. 145 Adams Avenue Hauppauge, NY 11788 USA

Main Tel: (631) 435-1110 Main Fax: (631) 435-1824

Support Team Fax: (631) 435-3388

www.centralsemi.com

Worldwide Field Representatives: www.centralsemi.com/wwreps

Worldwide Distributors:

www.centralsemi.com/wwdistributors

For the latest version of Central Semiconductor's **LIMITATIONS AND DAMAGES DISCLAIMER**, which is part of Central's Standard Terms and Conditions of sale, visit: www.centralsemi.com/terms

www.centralsemi.com (001)

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Central Semiconductor:

2N3710 2N3708 LEADFREE 2N3708 2N3707 2N3711