

Micro Commercial Components



Micro Commercial Components 20736 Marilla Street Chatsworth CA 91311

Phone: (818) 701-4933 Fax: (818) 701-4939 S9013-G S9013-H S9013-I

Features

- TO-92 Plastic-Encapsulate Transistors
- Capable of 0.625Watts(Tamb=25°C) of Power Dissipation.
- Collector-current 0.5A
- Collector-base Voltage 40V
- Operating and storage junction temperature range: -55°C to +150°C
- Marking Code: S9013
- Lead Free Finish/RoHS Compliant ("P" Suffix designates RoHS Compliant. See ordering information)
- Epoxy meets UL 94 V-0 flammability rating
- Moisure Sensitivity Level 1
- Halogen free available upon request by adding suffix "-HF"

Electrical Characteristics @ 25°C Unless Otherwise Specified

Parameter	Min	Max	Units	
OFF CHARACTERISTICS				
Collector-Base Breakdown Voltage 40			Vdc	
(l _c =100uAdc, l _E =0)				
Collector-Emitter Breakdown Voltage	25		Vdc	
$(l_c=0.1 \text{mAdc}, l_B=0)$				
Emitter-Base Breakdown Voltage	5.0		Vdc	
(ξ =100uAdc, ξ =0)				
Collector Cutoff Current		0.1	uAdc	
(V _{CB} =40Vdc, <u></u>				
Collector Cutoff Current		0.1	uAdc	
(V _{CE} =20Vdc, Ы=0)				
Emitter Cutoff Current		0.1	uAdc	
(V _{EB} =5.0Vdc,				
	Collector-Base Breakdown Voltage $(\c = 100 \mbox{L}=0)$ Collector-Emitter Breakdown Voltage $(\c = 0.1 \mbox{mAdc}, \c = 0)$ Emitter-Base Breakdown Voltage $(\c = 100 \mbox{L}=0)$ Collector Cutoff Current $(\c V_{\text{CB}}=40 \mbox{Vdc}, \c = 0)$ Collector Cutoff Current $(\c V_{\text{CE}}=20 \mbox{Vdc}, \c = 0)$ Emitter Cutoff Current	$ \begin{array}{llll} \textbf{Collector-Base Breakdown Voltage} & 40 \\ & ($	Collector-Base Breakdown Voltage $(\xi=100\text{uAdc}, \xi=0)$ Collector-Emitter Breakdown Voltage $(\xi=0.1\text{mAdc}, \xi=0)$ Emitter-Base Breakdown Voltage $(\xi=0.1\text{mAdc}, \xi=0)$ Eollector Cutoff Current $(\xi=0.1\text{mAdc}, \xi=0)$ Collector Cutoff Current $(\xi=0.1\text{mAdc}, \xi=0)$ Emitter Cutoff Current $(\xi=0.1\text{mAdc}, \xi=0)$ Collector Cutoff Current $(\xi=0.1\text{mAdc}, \xi=0.1\text{mAdc}, \xi=0.1$	

ON CHARACTERISTICS

h _{FE(1)}	DC Current Gain	64 400		
	(Ե=50mAdc, V _{CE} =1.0Vdc)			
h _{FE(2)}	DC Current Gain	40		
	(-500mAdc, V _{CE} =1.0Vdc)			
$V_{CE(sat)}$	Collector-Emitter Saturation Voltage		0.6	Vdc
	(l _c =500mAdc, l _B =50mAdc)			
$V_{BE(sat)}$	Base-Emitter Saturation Voltage		1.2	Vdc
	(b=500mAdc, l _B =50mAdc)			
V _{EB}	Base- Emitter Voltage		1.4	Vdc
	(上=100mAdc)			


SMALL-SIGNAL CHARACTERISTICS

f⊤	Transistor Frequency	150	 MHz
	($b=20$ mAdc, $V_{CE}=6.0$ Vdc, $f=30$ MHz)		

CLASSIFICATION OF HEE (1)

Rank	G	Н	
Range	112-166	144-202	190-300

NPN Silicon Transistors



DIMENSIONS					
	INCHI	ΞS	MM		
DIM	MIN	MAX	MIN	MAX	NOTE
Α	.175	.185	4.45	4.70	
В	.175	.185	4.45	4.70	
O	.500		12.70		
D	.016	.020	0.41	0.63	
Ш	.135	.145	3.43	3.68	
G	.095	.105	2.42	2.67	Straight Lead
G	.173	.220	4.40	5.60	Bent Lead

^{*} For ammo packing detailed specification, click here to visit our website of product packaging for details.



Micro Commercial Components

Ordering Information:

Device	Packing
Part Number-AP	Ammo Packing: 20Kpcs/Carton
Part Number-BP	Bulk: 100Kpcs/Carton

Note: Adding "-HF" suffix for halogen free, eg. Part Number-AP-HF

IMPORTANT NOTICE

Micro Commercial Components Corp. reserves the right to make changes without further notice to any product herein to make corrections, modifications, enhancements, improvements, or other changes. **Micro Commercial Components Corp.** does not assume any liability arising out of the application or use of any product described herein; neither does it convey any license under its patent rights, nor the rights of others. The user of products in such applications shall assume all risks of such use and will agree to hold **Micro Commercial Components Corp.** and all the companies whose products are represented on our website, harmless against all damages.

LIFE SUPPORT

MCC's products are not authorized for use as critical components in life support devices or systems without the express written approval of Micro Commercial Components Corporation.

CUSTOMER AWARENESS

Counterfeiting of semiconductor parts is a growing problem in the industry. Micro Commercial Components (MCC) is taking strong measures to protect ourselves and our customers from the proliferation of counterfeit parts. MCC strongly encourages customers to purchase MCC parts either directly from MCC or from Authorized MCC Distributors who are listed by country on our web page cited below. Products customers buy either from MCC directly or from Authorized MCC Distributors are genuine parts, have full traceability, meet MCC's quality standards for handling and storage. MCC will not provide any warranty coverage or other assistance for parts bought from Unauthorized Sources. MCC is committed to combat this global problem and encourage our customers to do their part in stopping this practice by buying direct or from authorized distributors.